

## covert monochrome camera in a smoke detector



### features

- ✓ sony 1/3" interline transfer monochrome CCD
- ✓ reverse voltage protection built-in
- ✓ smoke detector case with sideways view
- ✓ audio and video signals
- ✓ high resolution 600 TV lines
- ✓ wide range of lens options, 3.6mm fitted as standard
- ✓ 12V dc

### technical data

|                       |  |
|-----------------------|--|
| image sensor          | sony 1/3-inch interline monochrome CCD |
| horizontal resolution | 600TVL colour – 752 x 582 pixels       |
| electronic shutter    | 1/50 – 1/100,000 seconds               |
| sensitivity           | 0.1 lux @f1.2                          |
| signal to noise ratio | greater than 48dB (agc off)            |
| white balance         | automatic                              |
| Lens options          | 2.5mm to 16mm                          |
| power consumption     | 150mA                                  |
| video output          | 1V p-p ~ 75Ω                           |
| dimensions            | 130mm diameter x 58mm deep             |
| power supply          | 12V ± 10%                              |
| electrical            | built-in reverse polarity protection   |
| operating temperature | -10° C ~ +50° C                        |
| operating humidity    | 10% ~ 90%                              |

#### Genie CCTV Limited

Unit D city park, 26 watchmead, welwyn garden city, herts AL7 1LT  
 tel: +44(0) 1707 330541 fax +44(0) 1707 330543  
 website: [geniecctv.com](http://geniecctv.com) email: [info@geniecctv.com](mailto:info@geniecctv.com)